

V501, EDITION 3
 Prepared by the U.S. Army Topographic Command (BEGN), Washington, D.C. Compiled in 1955 by photogrammetric methods from aerial photographs taken 1953 and from U.S. Lake Survey Charts, 51 and 52, 1954-55; Windsor, Ontario, Canada, 1:253,440, 1943. Photographs field annotated 1954. United States area revised in 1971 by the U.S. Geological Survey from aerial photographs taken 1968-1970.
 Selected hydrographic data compiled from USC&GS charts. This information is not intended for navigational purposes.
 Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram.

LEGEND
 Figures in red denote approximate distances in miles between stars

POPULATED PLACES
 Over 500,000
 100,000 to 500,000
 25,000 to 100,000
 5,000 to 25,000
 1,000 to 5,000
 Less than 1,000

ROADS
 Primary, all-weather, hard surface
 Secondary, all-weather, hard surface
 Light-duty, all-weather, hard or improved surface
 Fair or dry weather, unimproved surface
 Trail
 Interchange

RAILROADS
 Standard gauge
 Narrow gauge
 Single track
 Double or Multiple track


BOUNDARIES
 International
 State or province
 County
 Park or reservation
 Mine

Landmarks: School; Church; Other
 Depth curve in feet
 Limit of danger; Reef
 Rocks; Awash
 Foreshore flat
 Intermittent or dry stream
 Marsh or swamp

Other symbols: Landplane airport, Landing area, Seaplane airport, Seaplane anchorage, Power line, Spot elevation in feet, Fishkill

Scale 1:250,000
 0 5 10 15 20 25 30 Statute Miles
 0 5 10 15 20 25 30 Kilometers
 0 5 10 15 20 Nautical Miles

CONTOUR INTERVAL 50 FEET
TRANSVERSE MERCATOR PROJECTION
 BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 17
 1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 34° (60 MILES) WESTERLY FOR THE CENTER OF THE WEST EDGE TO 54° (100 MILES) WESTERLY FOR THE CENTER OF THE EAST EDGE
 FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242



SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

GRID ZONE DESIGNATION:
 100,000 M. SQUARE IDENTIFICATION
 17T
 SAMPLE POINT: SILVERWOOD

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS
 1. Read letters identifying 100,000 meter square in which the point lies.
 2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
 3. Estimate meters from grid line to point.
 4. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
 5. Estimate meters from grid line to point.
 IF REPORTING BEYOND 50' IN ANY DIRECTION, prefix Grid Zone Designation, e.g., 17T1899

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 100 METERS
 1. Read letters identifying 100,000 meter square in which the point lies.
 2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
 3. Estimate meters from grid line to point.
 4. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
 5. Estimate meters from grid line to point.
 IF REPORTING BEYOND 50' IN ANY DIRECTION, prefix Grid Zone Designation, e.g., 17T1899

TOWNSHIP OR RANGE LINE
LAND GRANT BOUNDARY

FLINT, MICH., U.S.; ONTARIO, CAN.
 1954
 REVISED (U.S. AREA) 1971

Oct 04 1982
 3600