MIDLAND

EDITION 3

NK 16-3
SERIES V501

V501, EDITION 3

Prepared by the U.S. Army Topographic Command (BEGN), Washington, D.C. Compiled in 1955 by photogrammetric methods from aerial photographs taken 1953. Photographs field annotated 1954. Revised in 1971 by the U.S. Geological Survey from aerial photographs taken 1968-1970.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — BOSTON
- 100,000 to 500,000 — RICHMOND
- 25,000 to 100,000 — EVANSTON
- 5,000 to 25,000 — Hialeah
- 1,000 to 5,000 — Bar Harbor
- Less than 1,000 — Fishkill

RAILROADS
- Standard gauge, Single track, Double or Multiple
- Narrow gauge
- BOUNDARIES
- International
- State
- County
- Park or reservation

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

Landmarks: School; Church; Other
- Landplane airport
- Landing area
- Seaplane airport
- Orchard
- Woods-brushwood
- Mine
- Spot elevation in feet
- Marsh or swamp
- Intermittent or dry stream
- Power line

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 50 FEET

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 16

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 1° (20 MILS) WESTERLY FOR THE CENTER OF THE WEST EDGE TO 3½° (60 MILS) WESTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D.C. 20242

LOCATION DIAGRAM



SECTIONIZED TOWNSHIP

6	5	4	3	2	1	
7	8	9	10	11	12	
19	20	21	22	23	24	
18	17	16	15	14	13	
31	32	33	34	35	36	

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

JAN 9 1975

GRID ZONE DESIGNATION: 16T

100,000 M. SQUARE IDENTIFICATION

ED FD GD
EC FC GC

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number; example: 477000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: ASHLEY

1. Read letters identifying 100,000 meter square in which the point lies.
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself.
3. Estimate tenths from grid line to point.
4. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
5. Estimate tenths from grid line to point.

	GC	
	0	5
	8	6

SAMPLE REFERENCE: GC0586

If reporting beyond 10⁵ in any direction, prefix Grid Zone Designation, as: 16TGC0586

MIDLAND, MICHIGAN
1954
REVISED 1971

● INTERIOR—GEOLOGICAL SURVEY, RESTON, VIRGINIA—1974