



Mapped, edited, and published by the Geological Survey

Control by USGS and USC&GS
Planimetry of Michigan area by photogrammetric methods from aerial photographs taken 1958. Topography by photogrammetric methods from aerial photographs taken 1943. Field checked 1945. Revised 1962
Topography of Wisconsin area by photogrammetric methods from aerial photographs taken 1958. Field checked 1962

Polyconic projection. 1927 North American Datum
10,000-foot grid ticks based on Michigan coordinate system, north zone and Wisconsin coordinate system, north zone
1000-meter Universal Transverse Mercator grid ticks, zone 16, shown in blue

To place on the predicted North American Datum 1983
move the projection lines 7 meters north and
9 meters east as shown by dashed corner ticks

Map photoinspected 1980
No major culture or drainage changes observed



CONTOUR INTERVAL 20 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY
DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

AND BY THE GEOLOGICAL SURVEY DIVISION
MICHIGAN DEPARTMENT OF NATURAL RESOURCES, LANSING, MICHIGAN 48909
AND WISCONSIN GEOLOGICAL AND NATURAL HISTORY SURVEY, MADISON, WISCONSIN 53706
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION

Medium-duty — Light-duty
Unimproved dirt — State Route



NAULTS, MICH.-WIS.
N4552.5-W8822.5/7.5

1962
PHOTOINSPECTED 1980
DMA 3375 IV NW-SERIES V861

