



Mapped, edited, and published by the Geological Survey in cooperation with State of Michigan agencies. Control by USGS, USC&GS, and USCE. Planimetry by photogrammetric methods from aerial photographs. Topography by planimetric surveys 1940. Revised from aerial photographs taken 1966. Field checked 1967. Selected hydrographic data compiled from U.S. Lake Charts 37 (1965) and 370 (1967). This information is not intended for navigational purposes. Polyconic projection. 1927 North American datum. 10,000-foot grid based on Michigan coordinate system, south zone. 1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue. Red tint indicates areas in which only landmark buildings are shown. Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked. Map photosinspected 1978. No major culture or drainage changes observed.

SCALE 1:24,000
CONTOUR INTERVAL 5 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS LOW WATER 568.6 FEET
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092. A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST.

ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
Interstate Route U.S. Route State Route
QUADRANGLE LOCATION
To place on the predicted North American Datum 1983 move the projection lines 7 meters west as shown by dashed corner ticks.
Revisions shown in purple compiled from aerial photographs taken 1973. This information not field checked.
STONY POINT, MICH.
41083-H3-TF-024
PHOTOINSPECTED 1978
1967
PHOTOREVISED 1973
DMA 4367 IV NE—SERIES Y862

USGS NHD HISTORICAL MAP
JUL 25 1989
REC'D FILE COPY