



Mapped, edited, and published by the Geological Survey in cooperation with State of Michigan agencies  
Control by USGS, USC&GS, USCE, and Wayne County Highway Commission  
Planimetry by photogrammetric methods from aerial photographs  
Topography by planimeter surveys 1940. Revised from aerial photographs taken 1966. Field checked 1967  
Selected hydrographic data compiled from U. S. Lake Survey Charts 41 and 412 (1966). This information is not intended for navigational purposes  
Polyconic projection. 1927 North American datum  
10,000-foot grid based on Michigan coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue  
Red tint indicates areas in which only landmark buildings are shown

UTM GRID AND 1981 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET  
To place on the predicted North American Datum 1983 move the projection lines 7 meters west as shown by dashed corner ticks  
CONTOUR INTERVAL 5 FEET  
NATIONAL GEODETIC VERTICAL DATUM OF 1929  
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS RIVER SURFACE AT FOLLOWING STAGES: LAKE ST. CLAIR 571.7 AND LAKE ERIE 568.6  
SCALE 1:24 000  
1 000 0 1000 2000 3000 4000 5000 6000 7000 FEET  
1 KILOMETER

ROAD CLASSIFICATION  
Heavy-duty — Light duty  
Medium-duty — Unimproved dirt  
Interstate Route U.S. Route State Route  
QUADRANGLE LOCATION  
MICHIGAN

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092  
AND BY THE GEOLOGICAL SURVEY DIVISION  
MICHIGAN DEPARTMENT OF NATURAL RESOURCES, LANSING, MICHIGAN 48909  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

WYANDOTTE, MICH.—ONT.  
N4207.5—W8307.5/7.5  
1967  
PHOTOREVISED 1981  
DMA 4368 II NW—SERIES V862