



Maped, edited, and published by the Geological Survey
Revised in cooperation with State of Ohio agencies
Control by USGS and USC&GS
Topography by planetable surveys 1934. Revised 1965
Selected hydrographic data compiled from U. S. Lake Survey Charts
37 (1965) and 374 (1965). This information is not intended for
navigational purposes
Polyconic projection. 1927 North American datum
10,000-foot grids based on Ohio coordinate system, north zone
and Michigan coordinate system, south zone
1,000-meter Universal Transverse Mercator grid ticks, zone 17,
shown in blue
Fine red dashed lines indicate selected fence and field lines where
generally visible on aerial photographs. This information is unchecked
Red tint indicates areas in which only landmark buildings are shown
Entire area lies within the Michigan Survey. Land lines based on
the Michigan Meridian

SCALE 1:24,000
CONTOUR INTERVAL 5 FEET
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS LOW WATER 568.6 FEET
UTM GRID AND 1965 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET
29° 44' 29" N
113° 29' 29" W

USGS
Historical File
Topographic Division
ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt - - - -
Interstate Route U. S. Route State Route
OHIO
QUADRANGLE LOCATION
U.S.G.S.
TOPOGRAPHIC DIVISION
OREGON, OHIO-MICH.
N4137.5-W8322.5/7.5
1965
AMS 4367 III NW—SERIES V852

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

3560