



Mapped, edited, and published by the Geological Survey
 Control by USGS and USC&GS
 Topography by photogrammetric methods from aerial photographs taken 1964. Field checked 1965
 Polyconic projection. 1927 North American datum 10,000-foot grid based on Minnesota coordinate system, south zone 1000-meter Universal Transverse Mercator grid ticks, zone 15, shown in blue
 Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs
 This information is uncheckered
 To place on the predicted North American Datum 1983 move the projection lines 6 meters north and 17 meters east as shown by dashed corner ticks

SCALE 1:24,000
 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
 1 KILOMETER

CONTOUR INTERVAL 10 FEET
 NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION
 Heavy-duty ——— Light-duty ———
 Medium-duty ——— Unimproved dirt - - - - -
 U.S. Route (red circle) State Route (black circle)

UTM GRID AND 1965 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, RESTON, VIRGINIA, 22092
 A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS Historical File Topographic Division
 CLAREMONT, MINN. N4400—W9252.5/7.5 1965
 AMS 7472 III SW—SERIES V872

FEB 26 1981
 2000