



Produced by the United States Geological Survey
Control by USGS and NOS/NOAA
Topography by photogrammetric methods from aerial photographs taken 1947 and planetable surveys 1952. Revised from aerial photographs taken 1966. Field checked 1967.
Hydrography compiled from information furnished by Minnesota Department of Conservation.
Projection and 10,000-foot grid ticks: Minnesota coordinate system, south zone (Lambert conformal conic).
1000-meter Universal Transverse Mercator grid ticks, zone 15, shown in blue.
1927 North American Datum (NAD 27)
North American Datum of 1983 (NAD 83) is shown by dashed corner ticks.
The values of the shift between NAD 27 and NAD 83 for 7.5-minute intersections are given in USGS Bulletin 1875.
Red tint indicates areas in which only landmark buildings are shown.
Purple tint indicates extension of urban areas.

SCALE 1:24,000
1 0000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 KILOMETER
CONTOUR INTERVAL 10 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929
U.S. Regional Depository Copy DO NOT DISCARD
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225 OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
Interstate Route U.S. Route State Route
WHITE BEAR LAKE WEST, MINN.
SE/4 NEW BRIGHTON 15' QUADRANGLE
45093-A1-TF-024
1967
REVISED 1993
DMA 7374 II SE—SERIES V872

A.H. ROBINSON
MAP LIBRARY
JUN 10 1994
University of Wisconsin
Madison